



Gas Series

Perfect for:

Rental Stores • Truck Washes • In Plant Cleaning Systems • Chemical Processors • Warehouses



The Gas Series provides smooth, quiet performance with highly efficient results. These stationary units are available in natural gas or LP and are built tough for years of trouble-free service with energy conservation in mind.



COIL SYSTEM

Our exclusive "Cool Touch Coil" actually forms the combustion chamber, eliminating troublesome insulation and outside hot spots. It also allows for better air flow which in turn provides better fuel combustion and efficiency.



TEMPERATURE CONTROL

Easily control water temperature with dial control.

Standard all models except MXNH3010EBND (optional).



ACCUMULATOR ASSEMBLY

The Max Performance Accumulator Assembly effectively manages high-pressure flow conditions that may ordinarily cause system failure.

MODEL #	GPM	PSI	HP	VOLTS/PHASE	AMPS	GAS CONSUMPTION	STACK SIZE	DIMENSION	WEIGHT
MXNH3010EBND	3.0	1100	2.3	115/1	20	N-305 Cu. Ft. Per HR LP 3.5 GPH	10"	55"L x 26" W x 56"H	550 LBS
MXNH4020EBNA	4.0	2300	6.0	220/1	25	N-334 Cu. Ft. Per HR LP 3.8 GPH	12"	55"L x 26" W x 54"H	815 LBS
MXNH4020EBNB	4.0	2300	6.0	230/3	15	N-334 Cu. Ft. Per HR LP 3.8 GPH	12"	55"L x 26" W x 54"H	815 LBS
MXNH4020EBNC	4.0	2300	6.0	460/3	8	N-334 Cu. Ft. Per HR LP 3.8 GPH	12"	55"L x 26" W x 54"H	815 LBS
MXNH4030EBNA	4.0	3000	8.0	220/1	35	N-334 Cu. Ft. Per HR LP 3.8 GPH	12"	55"L x 26" W x 54"H	845 LBS
MXNH4030EBNB	4.0	3000	8.0	230/3	20	N-334 Cu. Ft. Per HR LP 3.8 GPH	12"	55"L x 26" W x 54"H	845 LBS
MXNH4030EBNC	4.0	3000	8.0	460/3	10	N-334 Cu. Ft. Per HR LP 3.8 GPH	12"	55"L x 26" W x 54"H	845 LBS
MXNH5030EBNB	5.0	3000	10.0	230/3	28	N-467 Cu. Ft. Per HR LP 5.4 GPH	12"	55"L x 26" W x 54"H	855 LBS
MXNH5030EBNC	5.0	3000	10.0	460/3	13	N-467 Cu. Ft. Per HR LP 5.4 GPH	12"	55"L x 26" W x 54"H	855 LBS

STANDARD FEATURES

- Heavy-duty frame with stainless steel panels
- Stainless steel coil wrap
- Heavy-duty triplex plunger pump
- Adjustable temperature control
- High efficiency electric motor
- High pressure detergent injector
- 50' high-pressure hose with quick disconnects
- 42" wand and shut-off gun
- Four color-coded quick-change spray nozzles

OPTIONS

- Hour meter
- Steam option – 250 degree
- Auto on/off with 30 sec. delay
- Remote control
- Auto shut down with adj. timer & complete shut down
- Soap solenoid
- Draft diverter
- LPG burner or natural gas burner
- Hose reel
- UL listed.

5 - 1 YEAR LIMITED WARRANTY

- 5 years on pump, Cool Touch Coil & frame
- 1 year – 90 days on remaining components



MAX-PERFORMANCE EQUIPMENT

200 EXECUTIVE DRIVE SUITE 160 WEST ORANGE, NJ 07052 USA

TEL. +1-973-325-3838 FAX +1-973-325-7974

Email: sales@max-performanceltd.com

#MXGS3-08